



Common Gate Camera



■ Normal lens type Lobby phone

[Color **KLP-C100 / KLP-C104 / KLP-C108 / KLP-C112**]
 [B/W **KLP-100 / KLP-104 / KLP-108 / KLP-112**]

- Upto 4 house (-104 type)
- Upto 8 houses (-108 type)
- upto 12houses (-112 type)
- Upto 450 houses connection (10key button type)
- Communication with guard master (10key button type)
- Door open function by access code (10 key button type) or by RF cards (option)
- Angle adjustment (up & down, right & left)
- Firm metal body case with new modern design
- Upto 3pcs of common gate cameras connection in a building
- Normal & Pinhole lens camera (KLP-PC, KLP-P series) selection

Specifications

Power	DC 17V	
Power consumption	Max. 5W	
Assurance temperature	-20°C ~ +50°C	
Image format	1/3CCD, 270,000 (NTSC, EIA) / 320,000 (PAL, CCIR) pixels	
TV system	NTSC (EIA) / PAL (CCIR)	
Lens	F:2.0, f=3.6mm	
Mim. illumination	0.1 lux on the object (IR LED ON)	
Mount type	Flush mount	
Dimension (mm)	120(W) x 255(H) x 39(D)	
Weight (approx. kg)	1.3kgs	
Monitor connection	Color camera	KIV-202, KIV-D202
	B/W camera	KIV-102, KIV-D102, KVM-520

• The product may include option or additional functions.